



# CL1 Series

M.2 2280 | NVMe PCIe SSD

## KEY BENEFITS

- High Performance NVMe PCIe
- Low latency
- Slim form factor— M.2 2280
- LDPC technology

## APPLICATIONS



Office Workloads



SQL Logging



PC Caching



Boot

## BREAK THE SATA BARRIER

Meet the perfect solid-state drive solution for boot and caching needs. The CL1 SSD Series with NVMe PCIe interface boosts your systems' performance by accelerating responsiveness, increasing productivity, and improving efficiency. NVMe delivers dramatic speed improvement as much as 7x faster than SATA SSDs. CL1 delivers superior speed with random read/write performance of up to 140,000/200,000 IOPS.

## SMALL BUT POWERFUL

With its small M.2 form factor, CL1 fits easily into a motherboard, no problem. Built to store your data efficiently and securely no matter what the file type, it operates more effectively than SATA SSDs, while also consuming less power.

## THE FIRMWARE ADVANTAGE

Our teams work closely with industry-leading chip manufacturers to develop solutions specific to your needs. With customized proprietary firmware, CL1 will provide superior performance at consistent speeds for years to come.

## QUALITY YOU CAN TRUST

Designed and manufactured in-house, we have dedicated teams and on-site testing capabilities for component and compatibility verification. This process ensures the quality each SSD and ability to operate successfully in a wide range of complex hardware and operating system environments.

## CL1 Series NVMe PCIe SSD

	CL1-8D128	CL1-8D256	CL1-8D512	CL1-8D1024
<b>Configuration</b>				
Capacity	128GB	256 GB	512 GB	1TB
Interface	NVMe PCIe Gen 3 x4			
Form Factor	M.2 2280			
<b>Performance</b>				
Sequential Read/Write <sup>1</sup>	1,400/800 MB/s	2,000/1,300 MB/s	2,000/1,300 MB/s	2,000/1,300 MB/s
4K Random Read/Write <sup>1</sup>	90K/140K IOPS	140K/200K IOPS	140K/200K IOPS	140K/200K IOPS
<b>Reliability</b>				
Power on/off cycles	50,000			
MTBF <sup>3</sup>	2 million hours			
Warranty	3 Years			
<b>Features</b>				
ECC	LDPC Gen 3 Engine			
S.M.A.R.T.	Supported			
NVMe Deallocate	Supported			
TCG-OPAL 2.0	Optional			
<b>Power Consumption</b>				
Idle/Active Mode	0.4 W/4 W			
Sleep Mode	5mW			
<b>Environment</b>				
Operating Temperature	0 to 70° C			
Non-operating Temperature	-40 to 85° C			
Power-On Ready <sup>3</sup>	500 ms			

Specifications and data are subject to change without notice. Product image is sample only. Not actual product.

<sup>1</sup>Based on internal testing, performance, may vary depending on host device, OS and application <sup>2</sup>UBER - Unrecovered Bit Error Rate <sup>3</sup>MTBF - Mean Time Between Failures based on parts stress analysis

For more information, please visit:

**ssstc.com**

**HEADQUARTERS**

12F, 392, Ruey Kuang Road, Neihu,  
Taipei 114, Taiwan R.O.C

**SOLID STATE STORAGE TECH. USA CORP.**

726 S. Hillview Dr., Milpitas, CA 95035  
ssd.ussupport@ssstc.com

© 2020 Solid State Storage Technology Corporation. All rights reserved.

Solid State Storage Technology Corporation (SSSTC) is a global leader in the design, development, and manufacturing of Solid State Drives (SSDs). SSSTC offers customized solutions to PC Client, Industrial Solutions, Enterprise/Data Center, and Cloud and Edge Computing markets.

All trademarks and registered trademarks are the property of their respective owners.